


H5 series

- Subminiature product, 105°C , 1000 hours
- Applicable to small electronic devices.
- Height: 5mm.
- RoHS Compliance
- 105°C , 超小型1000小時壽命產品。
- 適用於小型電子設備。
- 高度：5mm



SPECIFICATIONS


Items 項目	Characteristics 特性							
Capacitance Tolerance 靜電容量誤差	$\pm 20\%$ (120Hz,20°C)							
Operating Temperature Range 適用溫度範圍	-40 ~ +105°C							
Rated Voltage Range 額定電壓範圍	4 ~ 50VDC							
Leakage Current 洩漏電流	$I \leq 0.01CV$ or $3 (\mu A)$ which is greater.(After 2 minutes application of DC rated voltage, at 20 °C)							
Dissipation Factor 散逸因素($\tan \delta$)	Measurement Frequency: 120Hz. Temperature: 20°C							
	Rated Voltage(V)	4	6.3	10	16	25	35	50
	$\tan \delta$ (Max)	0.35	0.24	0.20	0.16	0.15	0.14	0.13
Low Temperature Stability 低溫特性	Measurement Frequency: 120Hz.							
	Rated Voltage(V)	4	6.3	10	16	25	35	50
Impedance Ratio(Max) 阻抗比率(最大值)	Z(-25°C)/Z(20°C)	6	3	3	2	2	2	2
	Z(-40°C)/Z(20°C)	12	8	5	4	3	3	3
Load Life 負荷壽命	1000hours,with application of rated voltage at 105°C							
	Capacitance Change	Within $\pm 20\%$ of Initial Value						
	$\tan \delta$	200% or less of Initial Specified Value						
	Leakage Current	Initial Specified Value or less						
Shelf Life 放置壽命	The following specifications shall be satisfied when the capacitors are restored to 20°C after exposing them for 500 hours 105°C without voltage applied. Before the measurement. The capacitance shall be preconditioned by applying voltage according to them 4.1 of JIS C 5101-4.							
	Capacitance Change	Within $\pm 20\%$ of Initial Value						
	$\tan \delta$	200% or less of Initial Specified Value						
	Leakage Current	Initial Specified Value or less						
Standards 參照標準	IEC 60384-4(JIS C 5101-4)							

Frequency Coefficient of Permissible Ripple Current

Capacitance (μF)	Frequency (Hz)			
	50	120	1K	$\geq 10K$
< 100	0.80	1.00	1.30	1.50
≥ 100	0.80	1.00	1.15	1.20

H5

H5 series

DIMENSIONS(mm)

ΦD	4	5	6.3	8
P	1.5	2.0	2.5	2.5
Φd	0.45	0.45	0.45	0.45

$$\alpha = 1.5$$

STANDARD RATINGS

D×L(mm) ; R.C.(mA rms) at 105°C 120Hz.

Cap (μF)	V	4		6.3		10		16	
	Item	D × L	R.C.	D × L	R.C.	D × L	R.C.	D × L	R.C.
10						4x5	16	4x5	18
22	4x5	20	4x5	21	4x5	25	4x5	33	
33	5x5	28	5x5	29	5x5	34	5x5	44	
47	5x5	33	5x5	34	6.3x5	46	6.3x5	52	
100	6.3x5	60	6.3x5	66	6.3x5	77	8x5	93	
150	6.3x5	67	6.3x5	75	8x5	100	8x5	115	
220	8x5	95	8x5	115	8x5	125			

Cap (μF)	V	25		35		50	
	Item	D × L	R.C.	D × L	R.C.	D × L	R.C.
0.47						4x5	3.7
1						4x5	6.2
2.2						4x5	10
3.3				4x5	11	4x5	14
4.7	4x5	13	4x5	16	5x5	18	
10	4x5	22	5x5	25	6.3x5	28	
22	6.3x5	38	6.3x5	46	6.3x5	59	
33	6.3x5	48	6.3x5	50	8x5	65	
47	6.3x5	58	8x5	69	8x5	78	